

## MIG A TWIST toortsen luchtgekoeld



Art nr	Omschrijving
00263150	ML150 TWIST 3m 0,8
00264150	ML150 TWIST 4m 0,8
00273150	ML150 TWIST R 3m 0,8
00274150	ML150 TWIST R 4m 0,8
00263250	ML250 TWIST 3m 0,8
00264250	ML250 TWIST 4m 0,8
00273250	ML250 TWIST R 3m 0,8
00274250	ML250 TWIST R 4m 0,8
Art nr	Omschrijving
00263240	ML 240 TWIST 3m 0,8
00264240	ML 240 TWIST 4m 0,8
00273240	ML 240 TWIST F 3m 0,8
00274240	ML 240 TWIST F 4m 0,8
00263300	ML 240 TWIST 3m 0,8
00264300	ML 300 TWIST 3m 1,0
00273300	ML 300 TWIST R 3m 1,0
00274300	ML 300 TWIST R 4m 1,0
00263360	ML360 TWIST 3m 1,0
00264360	ML360 TWIST 4m 1,0
00273360	ML360 TWIST R 3m 1,0
00274360	ML360 TWIST R 4m 1,0

R Regelbaar

### Technische data

MODEL TWIST	ML 150	ML 240	ML 250	ML 300	ML 360
Duty cycle CO <sub>2</sub> 60%	180 A	250 A	230 A	295 A	380 A
Duty cycle CO <sub>2</sub> 100%	160 A	225 A	205 A	260 A	340 A
Mixgas 60%	170 A	220 A	225 A	255 A	310 A
Mixgas 100%	150 A	195 A	200 A	225 A	270 A
Gas flow +/-5%	15 l/min.*	15 l/min.*	15 l/min.*	15 l/min.*	15 l/min.*
Wire diameter, mm	0.6-1.2	0.6-1.6	0.6-1.6	0.6-1.6	0.6-1.6
Cable, mm <sup>2</sup>	16	25	25	35	50
Weight	0.9 kg	1.2 kg	1.3 kg	1.6 kg	1.8 kg
Total weight kg, 3 m	1.8 kg	2.1 kg	2.1 kg	3.9 kg	4.0 kg
Connection	ZA	ZA	ZA	ZA	ZA

## MIG A TWIST toortsen watergekoeld



Art nr	Omschrijving
00266230	MV 240 TWIST 3m 1,0
00266240	MV 240 TWIST 4m 1,0
00276230	MV 240 TWIST F 3m 1,0
00276240	MV 240 TWIST F 4m 1,0
00263400	MV 400 FKS TWIST 3m 1,2
00264400	MV 400 FKS TWIST 4m 1,2
00274400	MV 400 FKS TWIST F 3m 1,2
00263500	MV 400 FKS TWIST F 4m 1,2
00264500	MV 500 FKS TWIST 3m 1,2
00273500	MV 500 FKS TWIST 4m 1,2
00274500	MV 500 FKS TWIST F 3m 1,2
80296701	MV 500 FKS TWIST F 4m 1,2

R Regelbaar

Art nr	Omschrijving
00263450	MV450 TWIST 3m 1,2 KD
00264450	MV450 TWIST 4m 1,2 KD
00273450	MV450 TWIST F 3m 1,2 KD
00274450	MV450 TWIST F 4m 1,2 KD
00263550	MV550 TWIST 3m 1,2 KD
00264550	MV 550 TWIST 4m 1,2 KD
00273550	MV550 TWIST F 3m 1,2 KD
00274550	MV550 TWIST F 4m 1,2 KD

### Technische data

MODEL TWIST	MV 240	MV 400 FKS	MV 450	MV 500 FKS	MV 550
Duty cycle CO <sub>2</sub> 60%	300 A	415 A	450 A	560 A	550 A
Duty cycle CO <sub>2</sub> 100%	300 A	415 A	450 A	560 A	550 A
Mixgas 60%	270 A	350 A	400 A	520 A	500 A
Mixgas 100%	270 A	350 A	400 A	520 A	500 A
Gas flow +/-5%	15 l/min.	18 l/min.	18 l/min.	18 l/min.	18 l/min.
Wire diameter, mm	0.6-1.8	0.8-2.4	0.6-3.2	0.8-2.4	0.6-3.2
Cable, mm <sup>2</sup>	16	16	16	16	16
Weight**	1.5 kg	1.6 kg	1.6 kg	1.7 kg	1.6 kg
Total weight kg, 3 m	3.0 kg	3.1 kg	3.0 kg	3.2 kg	3.0 kg
Connection	ZA	ZA	ZA	ZA	ZA